


3H 系列二位三通手扳阀



符号



型号命名

3H	2	10	—	08
型号/Model	系列代号/Series Code	位置/Position		接管螺纹
3H: 二位三通手扳阀 3H: 3/2 Way Hand Control Valve	2: 200系列/Series 3: 300系列/Series	10: 双位置/Two-Position		Port Thread
				06: G1/8"
				08: G1/4"
				10: G3/8"

举例

▲欲订购接管螺纹为G1/8",二位三通3H2系列手扳阀,其正确的订购码为: 3H210 - 06

技术参数

型号 / Model	3H210 - 06	3H210 - 08	3H310 - 08	3H310 - 10
工作介质/ Fluids	经过滤的压缩空气 / The constrigent after filtered			
位置数/ Position	二位三通/ 3/2 Way			
有效截面积/ Efficient Sectional Area	14mm ² (CV=0.78)	16mm ² (CV=0.89)	25mm ² (CV=1.4)	30mm ² (CV=1.68)
接管螺纹/Port Thread	进气/Supply=出气/Export=排气/Exhaust=G1/8"	进气/Supply=出气/Export=G1/4" * 排气/Exhaust=G1/8"	进气/Supply=出气/Export=排气/Exhaust=G1/4"	进气/Supply=出气/Export=G3/8" * 排气/Exhaust=G1/4"
润滑/ Lubrication	不需要/Not Required			
使用压力 / Operating Pressure	0~0.8MPa			
最大耐压力 / Max Pressure	1.2 MPa			
工作温度 / Operating Temperature	-5 - 60			

外形与安装尺寸

